





RGB LED Pool spotlight - 12V AC - 24W - Submersible - Remote control - IP68

Ref. B2120RGB

24W RGB LED pool light, surface mounted and specially designed to remain submerged.Equipped with a remote control to control its wide range of RGB colors.It has the highest protection of the market: IP68, guaranteeing its resistance and durability.With exceptional light quality, these pool lights are perfect for enhancing and beautifying aquatic areas in hotels, sports centers and more.Don't miss the opportunity to transform your aquatic spaces with style and efficiency!Suitable for salt and fresh water





Product data

Beam angle (°)120DimmableNoPower (W)24Nominal Voltage (V)12V ACDimensions (mm) LxlxhØ295x70MaterialPolycarbonateUse OutdoorYesIPIP68Temperature range-0°C ~ +55°CFrequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 yearsMountingSurface	Hue	RGB
Power (W)24Nominal Voltage (V)12V ACDimensions (mm) LxlxhØ295x70MaterialPolycarbonateUse OutdoorYesIPIP68Temperature range-0°C ~ +55°CFrequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Beam angle (°)	120
Nominal Voltage (V)12V ACDimensions (mm) LxlxhØ295x70MaterialPolycarbonateUse OutdoorYesIPIP68Temperature range-0°C ~ +55°CFrequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Dimmable	No
Dimensions (mm) LxlxhØ295x70MaterialPolycarbonateUse OutdoorYesIPIP68Temperature range-0°C ~ +55°CFrequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Power (W)	24
MaterialPolycarbonateUse OutdoorYesIPIP68Temperature range-0°C ~ +55°CFrequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Nominal Voltage (V)	12V AC
Use OutdoorYesIPIP68Temperature range-0°C ~ +55°CFrequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Dimensions (mm) Lxlxh	Ø295x70
IPIP68Temperature range-0°C ~ +55°CFrequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Material	Polycarbonate
Temperature range-0°C ~ +55°CFrequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Use Outdoor	Yes
Frequency of useNormalLifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	IP	IP68
Lifetime (h)25000Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Temperature range	-0°C ~ +55°C
Energy efficiency classFCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Frequency of use	Normal
CertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 years	Lifetime (h)	25000
Warranty According to legal guarantee: 2 years	Energy efficiency class	F
	Certificates	CE, ROHS
Mounting Surface	Warranty	According to legal guarantee: 2 years
	Mounting	Surface

