



## AR111 LED Bulb 30W external driver 2550lm

### Ref. B1002

QR111 LED bulb of 30W power with external LIFUD driver for optimal heat dissipation, improving its durability and performance. This type of luminaire usually requires installation on KARDAN, which serves to hold it and at the same time direct its light to the desired location. With an opening angle of 60°, neither too closed nor too open, it is ideal for all types of applications and locations, with high lighting requirements. Measurements: Ø111x89mm30W230V-ACCOB chip60°




### Product data

|                       |                                       |
|-----------------------|---------------------------------------|
| Hue                   | Cool white, Neutral white, Warm white |
| Kelvin (K)            | 3000, 6000, 4000                      |
| Lumens (Lm)           | 2550                                  |
| Efficiency (Lm/w)     | 85                                    |
| CRI                   | 80-85                                 |
| LED Type              | COB                                   |
| Dimmable              | No                                    |
| Power (W)             | 30                                    |
| Nominal Voltage (V)   | 230V-AC                               |
| Frequency (Hz)        | 50 - 60                               |
| Power factor (cosφ)   | 0,9                                   |
| Driver                | External                              |
| Socket                | AR111 / QR111                         |
| Dimensions (mm) LxLxh | 111x80                                |
| Material              | Aluminum                              |
| Diffuser material     | Plastic                               |
| Use Outdoor           | No                                    |
| IP                    | IP20                                  |



|                         |                                       |
|-------------------------|---------------------------------------|
| Temperature range       | -20°C ~ +40°C                         |
| Lifetime (h)            | 25000                                 |
| Energy efficiency class | A+ (2021)                             |
| Certificates            | CE, ROHS                              |
| Warranty                | According to legal guarantee: 2 years |

## Product variants

| Reference | Attributes                         |   |
|-----------|------------------------------------|---|
| B1002-BF  | Colour temperature - Cool White    |    |
| B1002-BN  | Colour temperature - Neutral White |    |
| B1002-BC  | Colour temperature - Warm White    |  |