

☆ Ċ 0 0 2 4 1 3


00 N L 0.5-2.0mm 4-5mm 2.4G 00-240VAC ax 0.1A MX5512 Signal Range: -30°C-+55°C DMX OUTPUT ROHS DMX OUTPUT D- D+ GND D- D+ 00000

0

DMX touch control panel - 4 zones - CCT


Ref. SK-T12

The 4-zone recessed DMX touch control panel offers complete lighting control for 100-240V CCT LED fixtures.lt can function as a DMX512 master or RF remote control.Its elegant, high-sensitivity glass touch interface includes a color wheel for precise adjustments, along with touch keys featuring LED indicators. Brightness, saturation, scene speed, dynamic modes, etc. can be adjusted.



Datos del producto

Nominal Voltage (V)100-240VDimensions (mm) Lxlxh86 x 86 x 33MaterialGlassUse OutdoorNoIPIP20Temperature range-30°C ~ +55°CCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 yearsMountingRecessedConnectivityRF, DMX	Dimmable	Yes
MaterialGlassUse OutdoorNoIPIP20Temperature range-30°C ~ +55°CCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 yearsMountingRecessed	Nominal Voltage (V)	100-240V
Use OutdoorNoIPIP20Temperature range-30°C ~ +55°CCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 yearsMountingRecessed	Dimensions (mm) Lxlxh	86 x 86 x 33
IPIP20Temperature range-30°C ~ +55°CCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 yearsMountingRecessed	Material	Glass
Temperature range-30°C ~ +55°CCertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 yearsMountingRecessed	Use Outdoor	No
CertificatesCE, ROHSWarrantyAccording to legal guarantee: 2 yearsMountingRecessed	IP	IP20
WarrantyAccording to legal guarantee: 2 yearsMountingRecessed	Temperature range	-30°C ~ +55°C
Mounting Recessed	Certificates	CE, ROHS
	Warranty	According to legal guarantee: 2 years
Connectivity RF, DMX	Mounting	Recessed
	Connectivity	RF, DMX
Colour control CCT	Colour control	CCT
Weight (kg) 0.181	Weight (kg)	0.181





Short press turn on zone light and select zone simultaneously, long press 2s turn off zone light. Short press multiple zone key fastly, will select multiple zone synchronously. 4 zone control seperately or synchronously, each zone could control multiple receivers.

Wiring Diagram for touch panel work as DMX 512 master