



RGBW/RGB/CCT/Single colour Controller 12-48V DC - 20A (5A/channel) - RF 2.4G - PUSH Dimmer - Skydance

Ref. SK-V4

4-channel RGBW / RGB / CCT / single colour controller for 12-48V LED luminaires. It features 10 preset dynamic modes. It offers smooth dimming from 0 to 100% without flickering and is compatible with 2.4G Skydance CCT RF remote controls. It's PUSH dimmable. It features 'auto-transmission' and 'auto-synchronization' functions, allowing it to send signals to other controllers and synchronize them when they are controlled by the same remote control.

Safety and EMC	
EMC standard (EMC)	ETSI EN 301 489-1 V2.2.3 ETSI EN 301 489-17 V3.2.4
Safety standard	EN 62368-1:2020+A11:2020
Radio Equipment (RED)	ETSI EN 300 328 V2.2.2
Certification	CE, EMC, RED

Product data

Power (W)	4 x (60-240)W
Nominal Voltage (V)	12-48VDC
Dimensions (mm) LxHxh	175 x 45 x 27
Use Outdoor	No
IP	IP20
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years, 5 years
Connectivity	RF
Number of channels	4
Maximum intensity (A)	5A/canal
Control Distance	30m

