



## CCT Controller - 12-24V DC - 2 channels - 5A/channel - RF 2.4GHz - Skydance

### Ref. SK-V2

2-channel CCT controller for 12-24V LED luminaires. It offers smooth dimming from 0 to 100% flicker-free and is compatible with CCT or single-color RF 2.4GHz Skydance remote controls. With auto-transmit and auto-sync functions that allow efficient and synchronized control.

| Safety and EMC        |   |
|-----------------------|---|
| EMC standard (EMC)    | ETSI EN 301 489-1 V2.2.3<br>ETSI EN 301 489-17 V3.2.4 |
| Safety standard       | EN 61348-1:2015+A1:2021<br>EN 61348-2-13:2014+A1:2017 |
| Radio Equipment (RED) | ETSI EN 300 328 V2.2.2                                |
| Certification         | CE, EMC, RED  |

### Product data

|                       |               |
|-----------------------|---------------|
| Power (W)             | 2 x (60-120W) |
| Nominal Voltage (V)   | 12-24V        |
| Use Outdoor           | No            |
| IP                    | IP20          |
| Temperature range     | -30°C ~ +55°C |
| Warranty              | 5 years       |
| Connectivity          | RF            |
| Colour control        | Monocolor     |
| Output voltage (V)    | 12-24VDC      |
| Number of channels    | 2             |
| Maximum intensity (A) | 5A/canal      |
| Control Distance      | 30m           |
| Length                | 97mm          |
| Width                 | 33mm          |
| Height                | 18mm          |

